

Last update: 2/18/25

Integrated Controls Package

Integrated control solutions are provided by the heat pump manufacturers for listing on the ICQPL. This is meant to ensure solutions are approved by the manufacturer and do not invalidate the manufacturer warranty for equipment installed.

To qualify, the IC must switch from heat pumps as the primary to the combustion system as the secondary. The changeover must be done automatically based on a preset outdoor temperature. The outdoor temperature can be determined by a local outdoor temperature sensor or via Wi-Fi weather data. For example, all ductless mini split heads in given heating zone must switch to existing boiler via IC communication with no user interaction.

Dual Fuel Thermostat

Dual fuel thermostats must be capable of doing at least two stages of heat and two stages of cooling and able to automate the changeover between the primary and secondary heat source based on an outdoor temperature. The temperature sensing can be via Wi-Fi weather data or via a local hard wired temperature sensor then it would be approved for the ICQPL.

Integrated Controls Package						
Manufacturer	Model Name	Model #	24v (Y/N)	Communicating (Y/N)	WiFi Enabled (Y/N)	Notes
Any IR Controlled Mini-split + Flair Aaon	Puck Pro VCCX	FLAIRPUCK001P VCCX	N	N	Y	Compatible Mini Split Brands and Compatible Smart Thermostats Listed at:
						flair.co/integrated-controls
						unit and the Flair system must be digitally cloud integrated with one of the following thermostats:
Aaon	VCCX	VCCX-2	Y	Y	N	
Aaon	VCCX	VCCX-IP	Y	Y	N	
Aaon	VCCX	VCCX2	Y	Y	N	
Aaon	VCCX	VCCX-454	Y	Y	N	
AprilAire	Zone Panel	6403	Y	N	N	Works with most brand thermostats to control conventional heat/cool or heat pump systems with electric or fossil fuel backup heating
AprilAire	Zone Panel	6404	Y	N	N	expandable up to twelve zones with additional #6401 panels. Works with most brand thermostats to control conventional heat/cool or
Amana Heating and Air Conditioning	Amana Smart Thermostat	ATST-CWE-BL-A	N	Y	Y	Compatible with all Amana Heating and Air conditioning brand communicating equipment
Arzel Zoning Technology	HeatPump Pro	PAN-HPP02	Y	N	N	Control Compatible with conventional Heat Pump and Dual Fuel Systems. The HeatPump Pro IC automatically switches from using heat pumps
Arzel Zoning Technology	HeatPump Pro	PAN-HPP03	Y	N	N	
Arzel Zoning Technology	HeatPump Pro	PAN-HPP04	Y	N	N	
Bosch	24V Interface	BMS-DRY-XXX	Y	Y	Y*	Thermostat and double pole double throw (DPDT) relay per indoor unit.*Wi-Fi Enabled based on the thermostat selected.
Bosch (Airzone)	Aidoo Pro	AZAI6WSPMD1	N	Y	Y	that have X-Y-E wiring. It can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the

[illegible]

[illegible]

Lennox Industries Inc.	CS7500 Commercial Thermostat	24K41	Y	N	N	Universal 4 Heat/3 Cool
LG Electronics	Third Party Tstst Method L Model Series IDU	PDRYCB300	Y	N	Optional	LG Option 1: PDRYCB300 + 24 V Trans. + Thermostat (1 Per IDU)
LG Electronics	Aux Heater Kit Highwall Multi	PRARS1	Y	Y	N	LG Option 2: Wall Units Multi Zone Idu Aux Htr Relay Prars1 (1 Per IDU)
LG Electronics	Aux Heater Kit All Ducted/Cassette	PRARH0	Y	Y	N	LG Option 3: Aux Htr Relay Prarh0 Ducted, Cassette Idu (1 Per IDU)
LG Electronics	Third Party Tstst Method A Model Series IDU	PDRYCB300	Y	N	Optional	LG Option 4: Arnu Series IDU PDRYCB300+ 24 V Trans. + Thermostat (1Per IDU)
LG Electronics (Airzone)	Aidoo Pro	AZAI6WSPLGE	N	Y	Y	ducted and non-ducted units that have a CN_REMO plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated
LG Electronics	A Series Idu Model - Dry Contact Built In	ALL "A" SERIES IDU	Y	Y	Y	LG Option 5: Arnu Series IDU + 2 Stage Tsat With Wired/Wireless/Internet Odt Sensing Wired Through Relay To Cn-Ext Of Any (1) IDU
LG MFG	Thermostat	PREMTVBC0	Y	Y	N	2 SET PT HTG&CLG 7DAY
LG MFG	Thermostat	PREMTBVC1	Y	Y	N	2 set pt htg&clg 7day/humid sensor opt-zigby occ sensors
LG MFG	Thermostat	PREMTC00U	Y	Y	N	Simple Thermostat
LG MFG	Thermostat	PREMTA000	Y	Y	N	Premium LG Thermostat
LG MFG	Dry Contact	PDRYCB320	Y	N	N	Dry contact for third party t-stat
	Kumo Station	PAC-WHS01HC-E				Requires an outdoor temperature sensor and each unit needs a Kumo Cloud interface
	Outdoor Temperature Sensor	C7089U1006/U				
Mitsubishi Electric	Kumo Cloud wireless interface	PAC-USWHS002-WF-1 or PAC-USWHS002-WF-2	N	N	Y	
	Thermostat Interface	PAC-US444CN-1 or PAC-US445CN-1				requires a t-stat interface and transformer for each indoor unit, and a 2 stage thermostat by any manufacturer. ACTS AS IC WITH QPL LISTED THERMOSTAT. To operate the indoor unit via Thermostat Interface (PAC-US444CN-1) using a 24VAC thermostat in the heat pump configuration (using O/B with Y1 & Y2 output)
Mitsubishi Electric	Transformer	VPL24-210	Y	Y*	Y*	Cloud with any IFTTT compatible thermostat. Current IFTTT compatible thermostats include Ecobee, and Honeywell as of 11/1/19. For list of
Mitsubishi Electric	Kumo Cloud with IFTTT compatible Thermostat	PAC-USWHS002-WF-1 PAC-USWHS002-WF-2	N	Y	Y	back-up heat thermostat to activate second stage on droop temperature. Outdoor balance point temperature can be set for CN24
Mitsubishi Electric	CN24 Relay Kit and compatible indoor units	CN24RELAY-KIT-CM3	Y	N	N	S-Series indoor units. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as
Mitsubishi Electric	Airzone	AZZBSR2MEL	N	Y	Y	ducted and non-ducted units that have a CN105 plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can
Airzone (Mitsubishi)	Aidoo Pro	AZAI6WSPMEL	N	Y	Y	https://doc.airzonecloud.com/Documentation/AZ6/Ai6/FT_AZAI6WSPMEL_MUL.pdf
Mitsubishi Electric	PAR-41MAAU Deluxe MA Remote Controller	PAR-41MAAU	N	Y	N	(CN24RELAY-KIT-CM3). - Select the outdoor air temperatures at which outdoor unit operation will be enabled and

Airzone (Mitsubishi)	VAF	AZVAFCB2MEL	N	Y	Y	S-Series indoor units. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as ANSI Z21.47/CSA 2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to AWS Cloud platform, known as 'MRCOOL Link.' This system requires the MRCOOL Smart Wi-Fi Mini-Stat (for MRCOOL minisplits) and the controller with the Mini-Split and a T Series Wi-Fi thermostat on the conventional HVAC system. This would be at a 1:1 relationship. There are no
Mitsubishi Electric	Intelli-HEAT Cased Coil	A18BA1, PAA-A24AA1, PAA-A24BA1, PAA-A30AA1, PAA-A30BA,	Y	N	N	
MRCOOL, LLC	MRCOOL Smart Wi-Fi Mini-Stat	MST05	Y	N	Y	
Resideo Technology Inc. under the Honeywell Home Brand	D6 Pro Wi-Fi Ductless Controller	DC6000WF1001/U	N	N	Y	
Rheem	Econet Smart Thermostat	RETST800SYS	Y	Y	Y	For use with Rheem communicating equipment only.
Samsung HVAC	Thermostat Adaptor	MIM-A60UN	Y	N	N	Requires T-Stat adaptor (maximum 2 indoor units per adaptor), 24VAC transformer, and dual fuel thermostat by any manufacturer.
Samsung HVAC	Samsung Wi-Fi Adapter	MIM-H04UN	N	Y	Y	CAC systems, FJM systems with Ducted, Cassette, and/or Console units connected. Once the Wifi adaptor is installed the Smart Things App can be used to connect to any of the following ST enabled thermostats from the following brands: 2gig, American Standard, Ecobee, Fibaro, Nest,
						https://www.smarthings.com/products-list listed on IC QPL. Integraton is possible by adding compatible thermostat to SmartThings App and automating
Samsung HVAC	SmartThings with SmartThings compatible Thermostat	All Samsung SmartThings-enabled Mini-splits, Heat Pumps, Cassettes, etc. See Notes for Models.	N	Y	Y	https://www.samsunghvac.com/products
Samsung HVAC (Airzone)	Aidoo Pro	AZAIGWSPSA2	N	Y	Y	ducted and non-ducted units that have F3 and F4 communication terminals. The Aidoo Pro can be used with any 3rd party thermostat and the
Trane	Symbio 700	X45091784001	Y	Y	Y	
Panasonic	Honeywell LYRIC	TH8732WFH5002/U	Y	Y	Y	Fossil Fuel Tstat For Panasonic IC QPL Solution
Panasonic	Honeywell LYRIC T6	TH6220WF2006	Y	Y	Y	Fossil Fuel Tstat For Panasonic IC QPL Solution
Panasonic	IFTTT Connect	PICDF19	N	Y	N	with a Panasonic mini-split and a Honeywell Lyric integrated with and auxiliary heat system. Installation contractors shall complete Panasonic
Pioneer	24V Interface	TST-24VIM-ECFMS	Y	Y	Y*	Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the Thermostat
Pioneer	IFTTT	TST-APWIFIMUSB TST-LCACWIFIKP	N	Y	Y	heat pump via the smartphone app, allowing for two-way communication between the mini split and the main heat source. Then an IFTTT applet
Pioneer (Airzone)	Aidoo Pro	PAZAIGWSP01	N	Y	Y	Pioneer ducted and non-ducted units that have X-Y-E wiring. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control
Pro1	755S	T755S	Y	No	No	Requires a R250s Wired Outdoor Sensor. Dual Fuel Balance Point can be set in the options.
Pro1	855sh	T855sh	Y	No	No	Requires a R250s Wired Outdoor Sensor. Dual Fuel Balance Point can be set in the options.
Pro1	855ish	T855ish	Y	No	Yes	Requires a R250s Wired Outdoor Sensor. Dual Fuel Balance Point can be set in the options.
Pro1	ProSync	T755WHO	Y	No	No	Requires a R250W Wireless Outdoor Sensor. Dual Fuel Balance Point can be set in the options

ZONEFIRST	Zone Control Panel	H32 & H32P	Y	N	N	Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and wi-fi heat pump thermostats. Panel has multiple staging options:													
ZONEFIRST	Zone Control Panel	MDP3	Y	N	N	to 100 Zones for Single and Two Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and wi-fi heat pump thermostats.													
ZONEFIRST	BLISS Zone System	BZS	Y	Y	Y	Combination Light Switch Thermostats (LST) for each zone for remote Wi-Fi control and monitoring of system operation. Heat Pump													

Dual Fuel Thermostats (Qualify as Integrated Controls with eligible Heat Pump/Furnace combinations)						
Manufacturer	Model Name	Model #	24v (Y/N)	Communicating (Y/N)	WiFi Enabled (Y/N)	Notes
Amana Heating and Air Conditioning	Amana Smart Thermostat	ATST-CWE-BL-A	N	Y	Y	Compatible with all Amana Heating and Air conditioning brand communicating equipment
American Standard	Gold 824	ACONT824AS52D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
American Standard	Silver 824	ACONT724AS42D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
American Standard	Platinum 850	ACONT850AC52U*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
American Standard	Platinum 1050	AZON1050AC52Z*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
American Standard	Link 360	ALINK360A2VVU*	N	Y	Y	Smart Thermostat (AHUI2360A200U*) and System Controller (TSYS2C60A2VVU*). Remote wired outdoor temp sensor BAYSENS01ATEMPA.
AprilAire	8446, 8448	8446, 8448	Y			Non-Programmable
AprilAire	8465, 8466, 8476	8476	Y			Programmable 5/2 or 5/1/1
AprilAire	8600, 8620, 8910	8600, 8620, 8910	Y			Programmable 7-Day
AprilAire	Thermostat	S86NMU	Y	N	N	dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable
AprilAire	Thermostat	S86NMUPR	Y	N	N	dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable
AprilAire	Wi-Fi Thermostat	S86WMUPR	Y	Y	Y	dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, Z100DT wireless outdoor
AprilAire	Thermostat	S84NSU	Y	N	N	dual fuel or 1H/1C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable
AprilAire	8476W, 8620W, 8910W, 8920W	8476W, 8620W, 8910W, 8920W	Y		Y	Programmable 7-Day
AprilAire	8800	8800	Y	Y		Programmable 7-Day

AprilAire	8810, 8820, 8830, 8840	8810, 8820, 8830, 8840	Y	Y	Y	Programmable 7-Day
Armstrong	Comfort Sync A3	507175-01	Y	Y	Y	Dual-fuel capable (Comfort Sync-enabled HP only) with two balance points.
Bosch	Bosch Connected Control BCC100 Thermostat	BCC100	Y	N	Y	Uses local weather for outdoor temperature and balance point
Bryant	Evolution System Control	SYSTXBBECC01	Y	Y	Y	
Bryant	COR	T6-WEM01-A	Y	N	Y	
Bryant	COR 5C	TSTWHA01	Y	N	Y	
Bryant	COR 7C	TSTWRH01	Y	N	Y	
Building36	Alarm.com Smart Thermostat	ADC-T2000	Optional	Y	Y	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled option. Dehumidifier and external baffle functionality
Building36	Alarm.com Smart Thermostat HD	ADC-T40K-HD	Y	Y	Y	4 heat and 2 cool and dual fuel capability. Cellular enabled option. Dehumidifier, Humidifier, external baffle, and vent control
Building36	Alarm.com Smart Thermostat (Design Studio Series)	ADC-T3000	Optional	Y	Y	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled option. Dehumidifier and external baffle functionality
Building36	Intelligent Thermostat	B36-T10	Optional	Y	N	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled
Carrier	COR	TP-WEM01-A	Y	N	Y	Uses local weather for outdoor Temperature and Change over
Carrier	COR 5C	TSTWHA01	Y	N	Y	Uses local weather for outdoor Temperature and Change over
Carrier	COR 7C	TSTWRH01	Y	N	Y	Uses local weather for outdoor Temperature and Change over
Carrier	Infinity System Control	SYSTXCCITC01-B, SYSTXCCWIC01-B	N	Y	Y	Available in black and white
Cielo WiGLE Inc.	Cielo Smart Thermostat	CT101WA	Y	N	Y	Cielo Smart thermostat fetches external weather data through cloud to enable the inerplay of appliances. (2) Cielo Smart Thermostats can also
Cielo WiGLE Inc.	Cielo Smart Thermostat ECO	TE101WA (White Color Variant), TE102WA (Black Color Variant)	Y	N	Y	Conventional Systems for up to 2 stages of Heating & 2 stages of Cooling. For Heat Pumps it supports up to 4 Stages of Heating and 2 Stages of Cooling. Cielo Smart Thermostats can also be linked to Cielo Breez Max and/or Cielo Breez PLUS (Cielo's smart thermostats for mini splits) using Cielo Linked (our cloud-based
Daikin	Daikin One Touch Smart Thermostat	DTST-TOU-A	N	Y	Y	Compatible with all Daikin brand communicating equipment
Daikin	One+	DTST-ONE-ADA-A	Y	Y	Y	Heat Pump Products. Thermostat is provided with communication adaptor that requires 110-240 VAC power supply. Additional adaptor https://cms.daikincomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf
Daikin	One+	DTST-CWBSA-NI-A	Y	Y	Y	Compatible with qualifying Daikin Central Heat Pump Systems. Refer to comprehensive guide at https://cms.daikincomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf

Daikin (Airzone)	DKN Plus Interface	AZAI6WSPDKC	N	Y	Y	units to a secondary heat source via onboard relay output. Secondary heat source can be enable via outdoor temperature configure with a
Daikin	Adaptive Touch Controller	BACRC-T-P01	Y	Y	N	units to an alternative heat source via onboard relay output.Controller required for each indoor unit. Can be used with outdoor temperature
Daikin	Adaptive Touch Controller	BACRC-TH-P01	Y	Y	N	units to an alternative heat source via onboard relay output.Controller required for each indoor unit. Can be used with outdoor temperature
Daikin	Adaptive Touch Controller	BACRC-THO-P01	Y	Y	N	units to an alternative heat source via onboard relay output.Controller required for each indoor unit. Can be used with outdoor temperature
Daikin	Adaptive Touch Controller	BACRC-THOC-P01	Y	Y	N	units to an alternative heat source via onboard relay output.Controller required for each indoor unit. Can be used with outdoor temperature
Daikin	Wiring Adaptor PCB	KRP1C74/75	N	N	N	units to a secondary heat source via onboard relay output. Install KRP1C74/75 with back up heat thermostat. Configure outdoor temperture https://daikinilibraryapi.daikincomfort.com/api/Download/GetDocument?id=f93267d4-303d-696b-9e5f-ff0000a9a572
Ecoer	Ecoer Smart Thermostat	EST1701	Y	Y	Y	Ecoer Heat Pump will enable fuel switching at a predetermined outdoor temperature. The Ecoer Heat pump has an onboard outdoor ambient
Ecoer	Ecoer Gateway	EG910L				communication device which transmits operating data from the Ecoer heat pump to the Ecoer monitoring computer. When enabled,
Ecobee	Ecobee 3 Lite	EB-STATE3LT***, EB-STATE3-01	Y	N	Y	Not a current model, but still available
Ecobee	Ecobee 4	EB-STATE4***	Y		Y	Ecobee 4 is now Ecobee Smart Thermostat, but Ecobee 4 is still available
Ecobee	Ecobee Smart Thermostat with Voice Control	EB-STATE5***	Y	N	Y	Model numbers may be slightly different due to color or vendor
Ecobee	Ecobee Thermostat	EB-STATE6***	Y	N	Y	color or vendor. External Temperature Detection, Time of Day Usage, Additional Home Temperature Sensor, Geofencing (User Device
Heil	Ion™ System Control	SYST0101CW	Y	Y	Y	
Honeywell Home	Prestige IAQ	YTHX9421R5085WW	Y		Y	Requires THM6000R7001 Internet Gateway
Honeywell Home	Prestige IAQ	YTHX9421R5101WW	Y		Y	Requires THM6000R7001 Internet Gateway
Honeywell Home	Smart Round	TH8732WFH 5002	Y	Y	Y	Use with C7089U Wired Outdoor Sensor
Honeywell Home	T6 Pro	TH6320U 2008	Y	N	N	Use with C7089U Wired Outdoor Sensor
Honeywell Home	T6 Pro Smart	TH6320WF 2003	Y	Y	Y	Two options: 1) Use with C7089U Wired Outdoor Sensor or 2) Use local weather thru WiFi for outdoor temp and changeover.
Honeywell Home	VisionPro 8000 Smart	TH8320R 1003	Y	Y	N/Y	Use with C7089R Wireless Outdoor Sensor. Needs HW Thm6000R 7001 Gateway For Wi-Fi
Honeywell Home	VisionPro 8000 Smart	TH8321R 1001	Y	Y	N/Y	Use with C7089R Wireless Outdoor Sensor. Needs HW Thm6000R 7001 Gateway For Wi-Fi
Honeywell Home	WiFi 9000	TH9320WF5003/U	Y	N	Y	Outdoor temperature and humidity via WiFi, appear after registration.
Honeywell Home	WiFi 8000	TH8321WF 1001	Y	N	Y	

Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel	HZ432	Y	N	N	Use with C7089U1006 outdoor sensor. Zone control for centrally ducted heat pump system.
Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel Kit	HZ432K	Y	N	N	Use with C7089U1006 outdoor sensor. Zone control for centrally ducted heat pump system.
Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel Kit	TZ-4	Y	N	N	system. A C7089B1000 Outdoor Temperature Sensor and a C7735A1000 Discharge Air Temperature Sensor are required for dual fuel
Honeywell Home/Resideo	T10+ Pro Smart Thermostat with RedLINK® 3.0 includes room sensor	THX321WFS3001W	Y	N	Y	
Honeywell Home/Resideo	T10 ProSmart with Redlink Sensor	THX321WFS2001W	Y	N	Y	Up to 3 Heat 2 Cool, 24v, with wireless indoor sensor, Can control Humidity or Ventillation
Honeywell Home/Resideo	T10 ProSmart	THX321WF2003W	Y	N	Y	Up to 3 Heat 2 Cool, 24v, with Humidity or Ventillation Control
Lennox Industries Inc.	S40 Smart Thermostat	22V24	Y	Y	Y	Universal 4 Heat/2 Cool/Variable Capacity
Lennox Industries Inc.	S30 Ultra Smart Thermostat	19V30	Y	Y	Y	Universal 4 Heat/2 Cool/Variable Capacity
Lennox Industries Inc.	E30 Smart Thermostat	15S63	Y	N	Y	Universal 4 Heat/2 Cool
Lennox Industries Inc.	M30 Smart Thermostat	15Z69	Y	N	Y	Universal 4 Heat/2 Cool
Lennox Industries Inc.	iComfort E30	E30	Y	N	Y	Universal Smart
Lennox Industries Inc.	iComfort M30	M30	Y	N	Y	Universal Smart
Lennox Industries Inc.	iComfort S30	S30	Y	Y	Y	Communicating Smart Thermostat
Lennox Industries Inc.	iComfort WiFi	WiFi	Y	Y	Y	Communicating Smart Thermostat
Lennox Industries Inc.	Harmony III	505,023M5	Y	Y	N	Zoning system
LG Electronics	Thermostat	PREMTVBC0	Y	Y	N	Integrated Control for entire hot water zone if connected to largest indoor unit of Multihead MSHF system.
LG Electronics	Thermostat	PREMTBVC1	Y	Y	N	Sensor OPT-ZIGBY OCC Sensors. Can act as Integrated Control for entire hot water zone if connected to largest indoor unit of Multihead
LG Electronics	Thermostat	PREMTBVC2	N	Y	N	2 set pt htg&clg 7day/humid sensor opt-zigby occ sensors
LG Electronics	Thermostat	PREMTBVC3	N	Y	N	2 set pt htg&clg 7day/humid sensor opt-zigby occ sensors
LG Electronics	Thermostat	PREMTA000	Y	Y	N	Premium LG Thermostat
LG Electronics	Thermostat	PREMTBVC4	N	Y	N	2 set pt htg&clg 7day/humid sensor + zigby occ sensors
LG Electronics	Thermostat	PREMTC00U	N	Y	N	Simple Thermostat
LG Electronics	Thermostat	PREMTB100	N	Y	N	Standard III Wired remote

LG Electronics	Thermostat	PREMTA200	N	Y	Y	Deluxe LG Thermostat
LG Electronics	Dry Contact	PDRYCB320	N	N	N	Dry contact for third party t-stat
LG Electronics (Airzone)	Aidoo Pro	AZAI6WSPLGE	N	Y	Y	ducted and non-ducted units that have a CN_REMO plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated
LG Electronics (Airzone)	VAF	AZVAFCB2LGE	N	Y	Y	units using the CN_REMO plug. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as
Mitsubishi Electric	Kumo Cloud with IFTTT compatible Thermostat	PAC-USWHS002-WF-1 or PAC-USWHS002-WF-2	N	Y	Y	Cloud with any IFTTT compatible thermostat. Current IFTTT compatible thermostats include Ecobee, and Honeywell as of 11/1/19. For list of
MRCOOL, LLC	MRCOOL Smart Thermostat	MST04	Y	N	Y	with conventional HVAC systems, supporting up to 2 stages of heating and 2 stages of cooling. For heat pump systems, it accommodates up to
Google	Nest Learning Thermostat (4th gen)	GA05169-US, GA05551-US, GA05171-US, GA05560-US	Y	Y	Y	The Nest Learning Thermostat (4th gen) works with most 24V systems, including gas, electric, oil, forced air, heat pump, and radiant.
Google Nest	Nest Learning Thermostat (3rd gen)	T3007ES, T3008US, T3016US, T3017US, T3021US	Y	Y	Y	
Google Nest	Nest Thermostat	GA02180-US	Y	N	Y	Programmable 7-day thermostat with guided setup. Installed using our "Pro Flow" install experience made for professionals. Heat Pump
Google Nest	Nest Thermostat	GA01334-US, GA02081-US, GA02082-US, GA02083-US	Y	Y	Y	The Nest Thermostat works with most 24V heating and cooling systems, including furnaces, air conditioners, boilers, and heat pumps with
Google Nest	Nest Thermostat E	T4000ES	Y	Y	Y	
Robertshaw	Robertshaw	9725I2	Y		Y	9725I2 Programmable Thermostat (3 Heat - 2 Cool)
Robertshaw	Robertshaw	9825I2	Y		Y	9825I2 Programmable Thermostat (3 Heat - 2 Cool)
Ruud	Econet Thermostat	ETST700SYS	Y	Y	Y	Amazon Alexa compatible for use with communicating Ruud equipment only.
Tekmar	Invita	564	Y	N	Y	2 wire stat with equipment interface
Tekmar	Invita	564B	Y	N	Y	same but black finish
Tekmar		557	Y	Y	Y	WiFi only with additional Gateway control
Tekmar		563	Y	N	Y	Stand alone with WiFi
Trane	XL 824	TCONT824AS52D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
Trane	XR 724	TCONT724AS42D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
Trane	XL 850	TCONT850AC52U*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
Trane	XL 1050	TZON1050AC52Z*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
Trane	Link 360	TLINK360A2VVU*	N	Y	Y	Smart Thermostat (THUI2360A200U*) and System Controller (TSYS2C60A2VVU*). Remote wired outdoor temp sensor BAYSENS01ATEMPA.

